Page: 1
Printed: 06/17/2019
Revision: 06/17/2019
Supersedes Revision: 09/07/2018

1. Product and Company Identification

Product Code: 414

Product Name: Lemon Oil Polish

Trade Name: SP #414

Manufacturer Information:

Company Name: Servpro Professional Cleaning Products,

LLC.

801 Industrial Blvd.

Gallatin, TN 37066 (800)535-5053

Emergency Contact: Infotrac

Supplier Name and Address: Phone Number:

Company Name: eaton chemical (816)741-7985

4124 Riverside Street Riverside, MO 64150

Emergency Contact: (800)424-9300

2. Hazards Identification

Acute Toxicity: Inhalation, Category 5
Acute Toxicity: Skin, Category 5

Serious Eye Damage/Eye Irritation, Category 2B

GHS Signal Word: Warning

GHS Hazard Phrases: H313 - May be harmful in contact with skin.

H320 - Causes eye irritation. H333 - May be harmful if inhaled.

GHS Precautionary Phrases: P264 - Wash hands thoroughly after handling.

GHS Response Phrases: P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell. P337+313 - If eye irritation persists, get medical advice/attention.

GHS Storage and Disposal

Phrases:

Inhalation: The toxicological properties of this substance have not been fully investigated. Aspiration

may lead to pulmonary edema.

Skin Contact: May cause skin irritation.

Eye Contact: May cause eye irritation.

Ingestion: May cause gastrointestinal irritation with nausea, vomiting and diarrhea. The

toxicological properties of this substance have not been fully investigated. Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal. Possible

aspiration hazard.

Page: 2 Printed: 06/17/2019 Revision: 06/17/2019

Supersedes Revision: 09/07/2018

3. Composition/Information on Ingredients

CAS # Hazardous Components (Chemical Name) Concentration

64742-06-9 Mineral oil, petroleum <=90.0 % 64742-65-0 Mineral oil <=10.0 %

4. First Aid Measures

Emergency and First Aid

Procedures:

In Case of Inhalation: Remove from exposure and move to fresh air immediately. If not breathing, give artificial

respiration. If breathing is difficult, give oxygen. Get medical aid if cough or other symptoms appear. Do NOT use mouth-to-mouth resuscitation. Possible aspiration

hazard.

In Case of Skin Contact: Flush skin with plenty of water for at least 15 minutes while removing contaminated

clothing and shoes. Get medical aid if irritation develops or persists. Wash clothing

before reuse.

In Case of Eye Contact: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and

lower eyelids. Get medical aid.

In Case of Ingestion: Never give anything by mouth to an unconscious person. Possible aspiration hazard. Get

medical aid. Do NOT induce vomiting. If conscious and alert, rinse mouth and drink 2-4

cupfuls of milk or water.

Signs and Symptoms Of

Exposure:

Mild irritation effect.

Note to Physician: Treat symptomatically and supportively.

5. Fire Fighting Measures

Flash Pt: 212.80 C

Explosive Limits: LEL: UEL:

Autoignition Pt: NP

Suitable Extinguishing Media: Use agent most appropriate to extinguish fire. Use water spray, dry chemical, carbon

dioxide, or appropriate foam.

Fire Fighting Instructions: As in any fire, wear a self-contained breathing apparatus in pressure-demand,

MSHA/NIOSH (approved or equivalent), and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

Flammable Properties and

Hazards:

Hazardous Combustion

Products:

Spilled:

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Use proper personal protective equipment as indicated in Section 8.

Spills/Leaks: Absorb spill with inert material (e.g. vermiculite, sand or earth), then place

in suitable container. Avoid runoff into storm sewers and ditches which lead to waterways. Clean up spills immediately, observing precautions in the Protective

Equipment section. Provide ventilation.

Page: 3 Printed: 06/17/2019 Revision: 06/17/2019

Supersedes Revision: 09/07/2018

7. Handling and Storage

Precautions To Be Taken in

Handling:

Wash thoroughly after handling. Use with adequate ventilation. Avoid prolonged or repeated contact with skin. Avoid contact with eyes, skin, and clothing. Keep container

tightly closed. Avoid ingestion and inhalation.

Precautions To Be Taken in

Storing:

Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from

incompatible substances.

8. Exposure Controls/Personal Protection

OSHA TWA **Partial Chemical Name ACGIH TWA** CAS# Other Limits

64742-06-9 Mineral oil, petroleum

64742-65-0 Mineral oil

Respiratory Equipment

(Specify Type):

A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace

conditions warrant respirator use.

Eye Protection: Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Protective Gloves: Wear appropriate protective gloves to prevent skin exposure.

Other Protective Clothing: Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls

(Ventilation etc.):

Facilities storing or utilizing this material should be equipped with an eyewash facility and

a safety shower. Use adequate ventilation to keep airborne concentrations low.

9. Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid

Yellow Clear Liquid. Appearance and Odor:

Lemon odor

:Ha

Melting Point: NA

Boiling Point: 392.00 C Flash Pt: 212.80 C

Evaporation Rate:

Flammability (solid, gas):

Explosive Limits: UEL: LEL:

Vapor Pressure (vs. Air or

mm Hg):

Vapor Density (vs. Air = 1):

Specific Gravity (Water = 1):

Solubility in Water:

0.99

Page: 4 Printed: 06/17/2019 Revision: 06/17/2019

Supersedes Revision: 09/07/2018

Octanol/Water Partition

Coefficient:

Autoignition Pt: NP Decomposition Temperature:

Viscosity:

10. Stability and Reactivity

Stability: Unstable [] Stable [X]

Conditions To Avoid - Incompatible r

Instability:

Incompatible materials, ignition sources, Excess heat.

Incompatibility - Materials To Oxidizing agents.

Avoid:

Hazardous Decomposition or Carbon monoxide, irritating and toxic fumes and gases.

Byproducts:

Possibility of Hazardous

Will occur []

Will not occur [X]

Reactions:

Conditions To Avoid - Hazardous Reactions:

11. Toxicological Information

Toxicological Information: Teratogenicity: No information available. Reproductive Effects: No information found.

Mutagenicity: Neurotoxicity:

Carcinogenicity/Other

Information:

CAS# 64742-65-0: Not listed by ACGIH, IARC, NTP, or CA Prop 65.

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

12. Ecological Information

13. Disposal Considerations

Waste Disposal Method: Chemical waste generators must determine whether a discarded chemical is classified

as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local

hazardous waste regulations to ensure complete and accurate classification.

RCRA P-Series: None listed. RCRA U-Series: None listed.

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name:

DOT Hazard Class: UN/NA Number:

LAND TRANSPORT (Canadian TDG):

TDG Shipping Name: No information available.

Page: 5
Printed: 06/17/2019
Revision: 06/17/2019
Supersedes Revision: 09/07/2018

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS # Hazardous Components (Chemical Name) S. 302 (EHS) S. 304 RQ S. 313 (TRI)

CAS # Hazardous Components (Chemical Name) Other US EPA or State Lists

 64742-06-9
 Mineral oil, petroleum
 CA PROP.65: No

 64742-65-0
 Mineral oil
 CA PROP.65: No

CAS # Hazardous Components (Chemical Name) International Regulatory Lists

64742-06-9 Mineral oil, petroleum Canadian DSL: Yes; Canadian NDSL: No 64742-65-0 Mineral oil Canadian DSL: Yes; Canadian NDSL: No

16. Other Information

Revision Date: 06/17/2019

Additional Information About

This Product: