



AF-S DX NIKKOR 55-300mm f/4.5-5.6G ED VR DX TELEPHOTO ZOOM LENS

At the heart of the Image™

AF-S DX NIKKOR 55-300mm f/4.5-5.6G ED VR
DX TELEPHOTO ZOOM LENS

FEATURES

- **Compact DX-format zoom lens with High Refractive Index (HRI) lens element, ED glass and VR II image stabilization**
Expanded photo and video opportunities that's designed to bring the action closer to the photographer.
- **5.5X Telephoto Zoom lens**
Ideal for capturing distant subjects at athletic events, family pictures, dramatic sunsets, travel and more. Angle of view equivalent to a focal length of 82.5 to 450mm in FX/35mm format D-SLR.
- **Nikon VR II Image Stabilization**
Vibration Reduction, engineered specifically for each VR NIKKOR lens, enables handheld shooting at up to 4 shutter speeds slower than would otherwise be possible, assuring dramatically sharper still images and video capture.
- **Tripod Detection Mode**
Reduces vibration that may occur due to shutter release when mounted on a tripod.
- **HRI (High Refractive Index) Lens Element**
HRI lens element is essential to keeping the lens compact while offering high contrast even at maximum aperture.
- **2 Extra-low Dispersion (ED) Elements**
Effectively minimizes chromatic aberration, even at the widest aperture settings.
- **Exclusive Nikon Silent Wave Motor (SWM)**
Enables fast, accurate and quiet autofocus.
- **Nikon Super Integrated Coating (SIC)**
Enhances light transmission efficiency and offers superior color consistency and reduces flare.
- **Minimum focus distance to 4.6 feet at all focal lengths**
- **Rounded 9-Blade Diaphragm**
Renders more natural appearance of out-of-focus image areas.



For more information visit nikonusa.com



AF-S DX NIKKOR 55-300mm f/4.5-5.6G ED VR DX TELEPHOTO ZOOM LENS

At the heart of the image™

SPECIFICATIONS | AF-S DX NIKKOR 55-300mm f/4.5-5.6G ED VR

Focal Length	55-300mm
Maximum Aperture	f/4.5-5.6
Minimum Aperture	f/22 (at 55mm), f/29 (at 300mm)
Lens Construction	17 elements in 11 groups
High Refractive Index (HRI) Lens Element	1
Picture Angle	28°50'-5°20'
Minimum Focus Distance	1.4 m/4.6 ft (throughout the entire zoom range)
Maximum Reproduction Ratio	0.28x
VR (Vibration Reduction) Image Stabilization	Yes. Provides up to 4 stops of compensation
Advanced Coating	Nikon Super Integrated Coating (SIC)
ED (Extra Low Dispersion) Elements	2
Focusing	Autofocus with Silent Wave Motor (SWM) and manual focus
Internal Focus (IF)	N/A
Aperture Control	Via camera Command Dial
Diaphragm Blades	9 (rounded)
Filter Attachment Size	58mm Screw-on
Dimensions (diameter x length)	(Approx.) 3.0 x 4.8 in. / 76.5x123 mm
Weight	(Approx.) 18.7 oz / 580g
Supplied Accessories	LF-1 Rear Lens Cap; Front Cap, HB-57 Snap-on Type Lens Hood; CL-1020 Soft Lens Case
Product Number	2197

nikonusa.com 800 NIKON UX SLR-2197-01-08/10

Note: Technical specifications and equipment are subject to change without any notice or obligation on the part of the manufacturer. Products and brand names are trademarks or registered trademarks of their respective companies. ©August 2010 Nikon Inc.

Nikon Inc. 1300 Walt Whitman Road Melville NY 11747