Nikon .

AF-S NIKKOR 85mm f/1.4G FX TELEPHOTO LENS

At the heart of the ímage™

- Ultra-fast classic portrait lens
 High performance FX-format f/1.4
 medium-telephoto lens is perfect
 for portraits, low-light applications
 offering beautiful Bokeh (background
 blur) and outstanding picture quality.
- Optimized for edge to edge sharpness on both FX and DX-format D-SLRs DX-format D-SLR angle of view is equivalent to a focal length of 127.5mm in FX/35mm format.
- Nano Crystal Coat
 Use of Nano Crystal Coat further reduces
 ghosting and interior flare across a wide range
 of wavelengths for even greater image clarity.
- M/A Focus Mode Switch Enables quick changes between manual and autofocus operation.
- Internal Focus (IF)
 Provides fast and quiet autofocus
 without changing the length of the lens,
 retaining working distance throughout
 the focus range.
- Exclusive Nikon Silent Wave Motor (SWM) Enables fast, accurate and quiet autofocus.
- Nikon Super Integrated Coating (SIC) Enhances light transmission efficiency and offers superior color consistency and reduced flare
- Rounded 9-Blade Diaphragm Renders more natural Bokeh (background blur)





AF-S NIKKOR 85mm f/1.4G FX TELEPHOTO LENS

At the heart of the image m

SPECIFICATIONS

AF-S NIKKOR 85mm f/1.4G

Focal Length 85mm

Maximum Aperture f/1.4

Minimum Aperture f/16

Lens Construction 10 elements in 9 groups

Picture Angle 28°30′ (18°50′ when used in DX Crop mode or

with DX-format D-SLRs)

Minimum Focus Distance 3 ft.(0.85 m)

Maximum Reproduction Ratio 0.12x

Advanced Coating Nikon Nano Crystal Coat (N), Nikon Super Integrated Coating (SIC)

Focusing Autofocus with Silent Wave Motor (SWM) and manual focus

Internal Focus (IF) Yes

Aperture Control Via camera Command Dial

Diaphragm Blades 9 (rounded)

Filter Attachment Size 77mm Screw-on

Dimensions (diameter x length) (Approx.) 3.4×3.3 in. $/86.2 \times 84$ mm

Weight (Approx.) 23.3 oz / 660g

Supplied Accessories LF-1 Rear Lens Cap; 77mm Cap, HB-55 Bayonet Lens Hood;

CL-1118 Semi-Soft Lens Case

Product Number 2195