



At the heart of the *image*™

AF-S NIKKOR 16-35mm f/4G ED VR WIDE-ANGLE ZOOM LENS

AF-S NIKKOR 16-35mm f/4G ED VR
WIDE-ANGLE ZOOM LENS

FEATURES

- **Definitive Wide-angle Zoom Lens**
Versatile wide-angle lens, perfect for travel, land and cityscapes, and general photography.
- **Nikon VR II (Vibration Reduction) Image Stabilization**
Vibration Reduction, engineered specifically for each VR NIKKOR lens, enables handheld shooting at up to 4 shutter speeds slower than would otherwise be possible, assuring dramatically sharper still images and video capture.
- **Nano Crystal Coat**
Further reduces ghosting and interior flare across a wide range of wavelengths for even greater image clarity.
- **2 Extra-low Dispersion (ED) Elements**
Offers superior sharpness and color correction by effectively minimizing chromatic aberration, even at the widest aperture settings.
- **3 Aspherical Lens Elements**
Aspherical lens elements virtually eliminate coma and other types of aberration, even when shooting at the widest available aperture.
- **Internal Focus (IF)**
Provides fast and quiet autofocus without changing the length of the lens, retaining working distance throughout the focus range.
- **Exclusive Nikon Silent Wave Motor (SWM)**
Enables fast, accurate and quiet autofocus.
- **M/A Focus Mode Switch**
Enables quick changes between manual and autofocus operation.
- **Rounded 9-Blade Diaphragm**
Renders more natural appearance of out-of-focus image elements.



For more information visit nikonusa.com



At the heart of the image™

AF-S NIKKOR 16-35mm f/4G ED VR

WIDE-ANGLE ZOOM LENS

SPECIFICATIONS

AF-S NIKKOR 16-35mm f/4G ED VR

Focal Length	16-35mm
Maximum Aperture	f/4
Minimum Aperture	f/22
Lens Construction	17 elements in 12 groups
Aspherical lens Elements	3
Picture Angle	107°-63°(83°-44° when used in DX Crop mode or with DX-format D-SLRs)
Minimum Focus Distance	0.95ft (0.29m) at a focal length of 16mm or 35mm 0.9ft (0.28m) at a focal length between 20mm and 28mm
Maximum Reproduction Ratio	0.25x
VR (Vibration Reduction) Image Stabilization	Yes. Provides up to 4 stops of compensation
Advanced Coating	Nikon Nano Crystal Coat (N)
ED (Extra-low Dispersion) Elements	2
Focusing	Autofocus with Silent Wave Motor (SWM) and manual focus
Internal Focus (IF)	Yes
Aperture Control	Via camera Command Dial
Diaphragm Blades	9 (rounded)
Filter Attachment Size	77mm Screw-on
Dimensions (diameter x length)	(Approx.) 3.2 x 4.9 in. / 82.5 x125mm
Weight	(Approx.) 24.0oz. / 680g
Supplied Accessories	LF-1 Rear Lens Cap; LC-77 Snap-on Front Lens Cap; HB-23 Bayonet Lens Hood; CL-1120 Semi-soft Case
Product Number	2182