

SAFETY DATA SHEET

1. IDENTIFICATION

Product Name Speedway VEP Heavy Duty Motor Oil

Synonym Speedway 5W-20 Motor Oil; All-Season 5W-20 Motor Oil; Performance Series 5W20 Motor

Oil; Speedway 5W-30 Motor Oil; All-Season 5W-30 Motor Oil; Performance Series 5W30 Motor Oil; Speedway 10W-30 Motor Oil; All-Season 10W-30 Motor Oil; Performance Series

10W30 Motor Oil; Speedway 10W-40 Motor Oil; All-Season 10W-40 Motor Oil;

Performance Series 10W40 Motor Oil; Speedway 20W-50 Motor Oil; All-Season 20W-50

Motor Oil; Performance Series 20W50 Motor Oil; 0116SPE012; 0118SPE012;

0125SPE012; 0126SPE012; 0127SPE012

Product code 0124SPE012 Chemical family 0124SPE012 Motor/Lube Oil

Recommended use Engine Oil. Restrictions on use Engine Oil.

Manufacturer, Importer, or Responsible Party Name and

Address

Speedway LLC P.O. Box 1500 Enon, OH 45501

SDS Information 1-937-863-7727

24 Hour Emergency Telephone CHEMTREC: 1-800-424-9300

2. HAZARD IDENTIFICATION

OSHA Regulatory Status

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Classification

Based on available data, the classification criteria are not met.

Hazards Not Otherwise Classified (HNOC)

Not applicable

Label Elements

No known significant effects or critical hazards.

Appearance Amber Liquid Physical State Liquid Odor Petroleum

Precautionary Statements - Prevention

Not applicable

Precautionary Statements - Response

Not applicable

SDS ID NO.: 0124SPE012 Product name: Speedway VEP Heavy Duty Motor Oil Page 1 of 8

Precautionary Statements - Storage

Not applicable

Precautionary Statements - Disposal

Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

Composition Information

Name	CAS Number	% Concentration
Base Lubricating Oils	Mixture	60-100

Motor oil is a complex mixture of highly refined lubricating base oil stocks (64742-52-5, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-70-7, 64741-88-4, 64742-01-4, 64742-65-0, 64741-95-3, 64742-62-7, 72623-83-7, 72623-86-0, 72623-87-1, 68037-01-4, 163149-28-8) and additives. All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.

4. FIRST AID MEASURES

First aid measures

General advice In case of accident or if you feel unwell, seek medical advice immediately (show directions

for use or safety data sheet if possible).

Inhalation Remove to fresh air and keep at rest in a position comfortable for breathing. If symptoms

occur get medical attention.

Skin contact Wash skin with plenty of soap and water. If irritation or other symptoms occur get medical

attention. Wash contaminated clothing and clean shoes before reuse.

Immediately flush eyes with plenty of water. Eyelids should be held away from the eyeball Eye contact

to ensure thorough rinsing. Gently remove contacts while flushing. Get medical attention if

irritation persists.

Rinse mouth out with water. If spontaneous vomiting occurs, keep head below hips, or if Ingestion

patient is lying down, turn body and head to side to prevent aspiration and monitor for breathing difficulty. Never give anything by mouth to an unconscious person. Keep affected

person warm and at rest. If symptoms develop, seek medical attention.

Most important signs and symptoms, both short-term and delayed with overexposure

Adverse effects Prolonged or repeated exposure may cause dermatitis, folliculitis or oil acne.

Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

For small fires, Class B fire extinguishing media such as CO2, dry chemical, foam Suitable extinguishing media

> (AFFF/ATC) or water spray can be used. For large fires, water spray, fog or foam (AFFF/ATC) can be used. Firefighting should be attempted only by those who are

adequately trained and equipped with proper protective equipment.

Do not use a solid water stream as it may scatter and spread fire. Unsuitable extinguishing media

Specific hazards arising from the

chemical

The product is not combustible per the OSHA Hazard Communication Standard, but will ignite and burn at temperatures exceeding the flash point.

SDS ID NO.: 0124SPE012 Product name: Speedway VEP Heavy Duty Motor Oil Page 2 of 8

Smoke, carbon monoxide, and other products of incomplete combustion. **Hazardous combustion products**

Explosion data

Sensitivity to mechanical

No.

impact:

Sensitivity to static discharge: No.

Special protective equipment and

precautions for firefighters

Avoid using straight water streams. Water spray and foam (AFFF/ATC) must be applied carefully to avoid frothing and from as far a distance as possible. Avoid excessive water spray application. Use water spray to cool exposed surfaces from as far a distance as

possible. Keep run-off water out of sewers and water sources.

Additional firefighting tactics Not applicable

NFPA Health 1 Flammability 1 Instability 0 Special Hazard -

6. ACCIDENTAL RELEASE MEASURES

Keep public away. Isolate and evacuate area. Shut off source if safe to do so. Personal precautions

Protective equipment Use personal protection measures as recommended in Section 8.

Advise authorities and National Response Center (800-424-8802) if the product has **Emergency procedures**

entered a water course or sewer. Notify local health and pollution control agencies, if

appropriate.

Avoid release to the environment. Avoid subsoil penetration. Do not allow material to **Environmental precautions**

contaminate ground water system or any surface water.

Methods and materials for

containment

Prevent further leakage or spillage if safe to do so.

Methods and materials for cleaning

up

Use suitable absorbent materials such as vermiculite, sand, or clay to clean up residual liquids. Recover and return free product to proper containers.

HANDLING AND STORAGE

Safe handling precautions

Avoid contact with skin, eyes and clothing. Do not swallow. Avoid breathing vapors or mists. Use good personal hygiene practices. Wash thoroughly after handling. Use personal protection measures as recommended in Section 8. Do not cut, drill, grind or weld on empty containers since explosive residues may remain. Refer to applicable EPA, OSHA, NFPA and consistent state and local requirements.

Lifetime, continuous skin contact with used motor oils has caused skin cancer in laboratory tests. In testing, thorough washing has been found to prevent the development of skin cancer from used motor oil exposure. Avoid excessive skin contact. Exercise good personal hygiene including the removal and washing of soiled clothing and destroy used motor oil

contaminated leather shoes/boots.

Store in properly closed containers that are appropriately labeled and in a cool. Storage conditions

well-ventilated area. Containers that have been opened must be carefully resealed and kept

upright to prevent leakage. Store away from incompatible materials.

Strong oxidizing agents. Incompatible materials

EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

SDS ID NO.: 0124SPE012 Product name: Speedway VEP Heavy Duty Motor Oil Page 3 of 8

Notes: No further information available.

Engineering measures Local or general exhaust required when using at elevated temperatures that generate

vapors or mists.

Personal protective equipment

Eye protection Use goggles or face-shield if the potential for splashing exists.

Skin and body protectionUse nitrile rubber, Viton® or PVA gloves for repeated or prolonged skin exposure. Glove

suitability is based on workplace conditions and usage. Contact the glove manufacturer for specific advice on glove selection and breakthrough times. Wear appropriate protective

clothing.

Respiratory protectionUse a NIOSH approved organic vapor chemical cartridge or supplied air respirators when

there is the potential for airborne exposures to exceed permissible exposure limits or if excessive vapors are generated. Observe respirator assigned protection factors (APFs) criteria cited in federal OSHA 29 CFR 1910.134. Self-contained breathing apparatus should

be used for fire fighting.

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes and clothing. Wash hands before breaks and immediately after handling the

product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

AppearanceAmber LiquidPhysical StateLiquidColorAmberOdorPetroleumOdor ThresholdNo data available.

Property
pH
No available data.
Melting Point / Freezing Point
Initial Boiling Point / Boiling Range
No data available.
No data available.

Flash Point $> 200 \, ^{\circ}\text{C} \, / > 392 \, ^{\circ}\text{F} \, (ASTM \, D92)$

Evaporation Rate No data available. Flammability (solid, gas) Not applicable.

Flammability Limit in Air (%):

Upper Flammability Limit:
Lower Flammability Limit:
No data available.
No data available.
No data available.
No data available.
Vapor Pressure
Vapor Density
No data available.
No data available.

Specific Gravity / Relative Density 0.87

Water Solubility
Partition Coefficient
Autoignition Temperature
Decomposition Temperature
No data available.
No data available.
No data available.

Kinematic Viscosity 175 cSt @ 40°C (ASTM D445)

VOC Content (%) No data available.

10. STABILITY AND REACTIVITY

Reactivity The product is non-reactive under normal conditions.

Chemical stability Stable under recommended storage conditions.

SDS ID NO.: 0124SPE012 Product name: Speedway VEP Heavy Duty Motor Oil Page 4 of 8

Possibility of hazardous reactions None under normal processing.

Hazardous polymerization Will not occur.

Conditions to avoid Sources of heat or ignition.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products None known under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Potential short-term adverse effects from overexposures

Inhalation Overheating may produce vapors which may cause respiratory irritation, dizziness and

nausea.

Exposure to vapor or contact with liquid may cause mild eye irritation, including tearing,

stinging, and redness.

Skin contact Prolonged or repeated contact may dry skin and cause irritation.

Ingestion May cause irritation of the mouth, throat and gastrointestinal tract.

Acute toxicological data

No data available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

This product is considered to have a low order of acute and chronic toxicity under normal use and storage conditions

USED MOTOR OIL: Lifetime, continuous skin contact with used motor oils has caused skin cancer in laboratory tests. The combustion process produces compounds (polycyclic aromatic hydrocarbons) in motor oils that increase with use and are responsible for the cancer induction. Thorough washing has been found to prevent the development of skin cancer on animals from used motor oil exposure.

Adverse effects related to the physical, chemical and toxicological characteristics

Signs and symptoms Prolonged or repeated exposure may cause dermatitis, folliculitis or oil acne.

Acute toxicity None known.

Skin corrosion/irritation None known.

Serious eye damage/eye irritation None known.

Sensitization None known.

Mutagenic effects None known.

Carcinogenicity None known.

Reproductive toxicity None known.

Specific Target Organ Toxicity

(STOT) - single exposure

None known.

Specific Target Organ Toxicity (STOT) - repeated exposure

None known.

SDS ID NO.: 0124SPE012 Product name: Speedway VEP Heavy Duty Motor Oil Page 5 of 8

Aspiration hazard None known.

12. ECOLOGICAL INFORMATION

Ecotoxicity Used motor and/or lube oils can be toxic to birds and fish.

Bioaccumulation Has the potential to bioaccumulate.

Mobility in soil

No information available.

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Description of waste residues No information available.

Safe handling of wastes Handle in accordance with applicable local, state, and federal regulations. Use personal

protection measures as required.

Disposal of wastes / methods of

disposal

The user is responsible for determining if any discarded material is a hazardous waste (40 CFR 262.11). Dispose of in accordance with federal, state and local regulations.

Contaminated packaging disposal Empty containers should be completely drained and then discarded or recycled, if possible.

Do not cut, drill, grind or weld on empty containers since explosive residues may be

present. Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT

UN/Identification No:
UN Proper Shipping Name:
Transport Hazard Class(es):
Packing Group:

Not applicable
Not applicable
Not applicable

<u>IATA</u>

UN/Identification No:Not applicableUN Proper Shipping Name:Not RegulatedTransport Hazard Class(es):Not applicablePacking Group:Not applicable

IMDG

UN/Identification No:
UN Proper Shipping Name:
Not applicable
Not Regulated
Transport Hazard Class(es):
Not applicable
Packing Group:
Not applicable
No
No

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable

15. REGULATORY INFORMATION

Regulatory Information

US TSCA Chemical InventoryThis product and/or its components are listed on the TSCA Chemical Inventory or are

exempt.

SDS ID NO.: 0124SPE012 Product name: Speedway VEP Heavy Duty Motor Oil Page 6 of 8

Canada DSL/NDSL Inventory

This product and/or its components are listed either on the Domestic Substances List (DSL)

or are exempt.

EPA Superfund Amendment & Reauthorization Act (SARA)

SARA Section 302 This product does not contain any component(s) included on EPA's Extremely Hazardous

Substance (EHS) List above the de minimis threshold.

SARA Section 304 This product does not contain any component(s) identified as an EHS or a CERCLA

Hazardous substance above the de minimis threshold.

SARA Section 311/312 The following EPA hazard categories apply to this product:

None

SARA Section 313 This product does not contain components subject to the reporting requirements of SARA

TItle III Section 313 Toxic Release Inventory Reporting Form R) above the de minimis

threshold.

U.S. State Regulations

California Proposition 65 This product can expose you to chemicals which are known to the State of California to

cause cancer, birth defects or other reproductive harm.

For more information, go to www.P65Warnings.ca.gov.

State Right-To-Know Regulations The following component(s) of this material are identified on the regulatory lists below:

Name	New Jersey Right-To-Know	Pennsylvania Right-To-Know	Massachusetts Right-To Know
Motor Oil MIXTURE	Listed	Not Listed	Not Listed
Highly Refined Mineral Base Oil 64742-55-8	Not Listed	Not Listed	Listed
Distillates, Petroleum Solvent-dewaxed Light Paraffinic 64742-56-9	Not Listed	Not Listed	Listed
Paraffin Oils, Petroleum Catalytic Dewaxed Heavy 64742-70-7	Not Listed	Not Listed	Listed

16. OTHER INFORMATION

Prepared by Toxicology & Product Safety

NFPA



Revision Notes

SDS ID NO.: 0124SPE012 Product name: Speedway VEP Heavy Duty Motor Oil Page 7 of 8

Revision date 05/01/2020 Previous publish date 05/01/2020

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is intended as guidance for safe handling, use, processing, storage, transportation, accidental release, clean-up and disposal and is not considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SDS ID NO.: 0124SPE012 Product name: Speedway VEP Heavy Duty Motor Oil Page 8 of 8