

**SECTION 09 7733**  
**GLASS FIBER REINFORCED PLASTIC PANELS**

**PART 1 GENERAL**

**1.01 SECTION INCLUDES**

- A. Glass fiber reinforced plastic panels.
- B. Trim.

**1.02 REFERENCE STANDARDS**

- A. ASTM D5319 - Standard Specification for Glass-Fiber Reinforced Polyester Wall and Ceiling Panels; 2012.
- B. ASTM E84 - Standard Test Method for Surface Burning Characteristics of Building Materials; 2015a.

**1.03 SUBMITTALS**

- A. See Section 01 3000 - Administrative Requirements, for submittal procedures.
- B. Product Data: Provide data on specified products, describing physical and performance characteristics; including sizes, patterns and colors available; and installation instructions.

**1.04 DELIVERY, STORAGE, AND HANDLING**

- A. Store panels flat, indoors, on a clean, dry surface. Remove packaging and allow panels to acclimate to room temperature for 48 hours prior to installation.

**PART 2 PRODUCTS**

**2.01 PANEL SYSTEMS**

- A. Wall Panels:
  - 1. Panel Size: 4 by 8 feet.
  - 2. Panel Thickness: 0.10 inch.
  - 3. Surface Design: Embossed.
  - 4. Color: White.
  - 5. Attachment Method: Adhesive only, sealant joints, no trim.

**2.02 MATERIALS**

- A. Panels: Glass fiber reinforced plastic (FRP), complying with ASTM D5319.
  - 1. Surface Burning Characteristics: Maximum flame spread index of 25 and smoke developed index of 450; when system tested in accordance with ASTM E84.
- B. Trim: Vinyl; color coordinating with panel.
- C. Sealant: Type recommended by panel manufacturer; white.

**PART 3 EXECUTION**

**3.01 INSTALLATION - WALLS**

- A. Install panels in accordance with manufacturer's instructions.
- B. Cut and drill panels with carbide tipped saw blades, drill bits, or snips.
- C. Apply adhesive to the back side of the panel using trowel as recommended by adhesive manufacturer.
- D. Apply panels to wall with seams plumb and pattern aligned with adjoining panels.
- E. Install panels with manufacturer's recommended gap for panel field and corner joints.
- F. Place trim on panel before fastening edges, as required.
- G. Fill channels in trim with sealant before attaching to panel.
- H. Install trim with adhesive and screws or nails, as required.
- I. Seal gaps at floor, ceiling, and between panels with applicable sealant to prevent moisture intrusion.

J. Remove excess sealant after paneling is installed and prior to curing.

**END OF SECTION 09 7733**