

# Premium Cotton Picker Grease

## **Cotton Picker Grease**



Premium Cotton Picker Grease is a light green, smooth textured, premium quality grease formulated from selected materials which provide protection from oxidation, wear, rust and corrosion as well as ensuring freedom from sticky, water soluble deposits. In addition, a specially incorporated additive helps reduce sliding wear throughout the mechanisms of the cotton picker. Premium Cotton Picker Grease Is formulated and manufactured to provide superior pumpability in cotton harvesting equipment.

## **Applications**

Premium Cotton Picker Grease is designed for use in picker spindles, picker bars and ancillaries of Case, IHC and John Deere mechanical cotton pickers.

Useable temperature range in continuous service is -20 to 120°C.

### **Benefits**

- Minimises consumption as its consistency provides full lubrication, while reducing wastage.
- Resists oxidation, rust and corrosion particularly in the presence of vegetable saps.
- Less cotton stain as the grease does not leak or splash on cotton.
- Reduces wear, providing longer life for bearings and spindle gears.
- Good penetration into bearings due to the low viscosity base oil provides low starting resistance in colder weather and correct picker speed operation.
- Low co-efficient of friction which means less stress on the drivetrain.
- Good pumpability

### **Performance Standards**

Suitable for use where these performance standards are recommended JI Case B-27 John Deere JD 305, JD 360, JD 380

### **Typical Characteristics**

Product Code	5349
NLGI Grade	00
Penetration, Worked	400 - 430
Colour	Green
Dropping Point, °C	190
Mineral Oil Viscosity, cSt at 40°C	32
Four Ball Scar Diameter, mm	0.42

### Pack Size

850 kg





# **Environment Health and Safety**

Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

## **Other Information**

For further information on Ampol products and services call the Technical Solutions on 1300 364 169.

Information in this publication is accurate at the time of printing and reasonable care has been taken to ensure it is complete and accurate. However, this information is subject to change (such as when formulations or usage and storage information changes). Please visit www.ampol.com.au for the latest product information. Independent advice should be sought before taking any action in reliance on the information in this publication, and Ampol Australia Limited and its related bodies corporate accept no liability for any reliance on this publication's content.