SECTION 1: Product identifier

1.1. GHS Product identifier

Product form	Mixture
Product name	XPEL Edge Prep Can

1.2. Other means of identification

Other means of identification	XPEL-003C

1.3. Recommended use of the chemical and restrictions on use

Recommended Use	Adhesion promotor

1.4. Details of manufacturer or importer

Supplier
XPEL, Inc.
3251 I-35
San Antonio, TX, 78219
USA
T +1 210-678-3700

Supplier
XPEL Australia
4/2 Holker St.
Newington NSW 2127
Australia

E-mail address of competent person responsible for the SDS: sds@gbk-ingelheim.de

1.5. Emergency phone number

Emergency number	1300 366 961

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 2	H225
Reproductive toxicity, Category 2	H319
Skin corrosion/irritation, Category 2	H361
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU)

Flame | Exclamation mark | Health hazard

Signal word (GHS AU)	Danger
Contains	Ethylacetate (60 - 100 %); Toluene (≥ 1 – < 10 %); Propan-2-ol (≥ 0.1 – < 3 %)
Hazard statements (GHS AU)	H225 - Highly flammable liquid and vapour
	H319 - Causes serious eye irritation

	H336 - May cause drowsiness or dizziness
	H361 - Suspected of damaging the unborn child.
Precautionary statements (GHS AU)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof lighting, ventilating, electrical equipment.
P261	Avoid breathing vapours, mist, dust, spray.
P264	Wash hands, forearms and face thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing, eye protection, face protection.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER, a doctor if you feel unwell.
P337 + P313	If eye irritation persists: Get medical attention.
P370 + P378	In case of fire: Use media other than water to extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

Name	CAS No	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Ethylacetate	141-78-6	60 - 100	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Toluene	108-88-3	≥ 1 – < 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Propan-2-ol	67-63-0	≥ 0.1 – < 3	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	Call a poison center or a doctor if you feel unwell.

4.2. Symptoms caused by exposure

Symptoms/effects	May cause drowsiness or dizziness.
Symptoms/effects after eye contact	Causes serious eye irritation.
Chronic symptoms	Suspected of damaging the unborn child.

4.3. Medical attention and special treatment

Treatment	Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable Extinguishing Media	Do not use a solid water stream as it may scatter and spread fire.

5.2. Specific hazards arising from the chemical

Fire hazard	Highly flammable liquid and vapour.
Explosion hazard	Product is not explosive.
General measures	Avoid contact with eyes, skin or mucous membrane. Evacuate the danger area. Evacuate personnel to a safe area.
Hazardous decomposition products in case of fire	Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Hazchem Code	* 3Y

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Avoid contact with eyes, skin or mucous membrane. Evacuate the danger area. Evacuate personnel to a safe area.
6.1.1. For non-emergency personnel Emergency procedures	Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours, mist, dust, spray. Avoid contact with skin and eyes.
6.1.2. For emergency responders Protective equipment	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: “Exposure controls/personal protection”.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up	Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	Avoid contact with eyes, skin or mucous membrane.
Precautions for safe handling	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Avoid breathing vapours, mist, dust, spray. Avoid contact with skin and eyes.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	Ground/bond container and receiving equipment.
Storage conditions	Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Heat and ignition sources	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Information on mixed storage	Keep away from food, drink and animal feeding stuffs.
Storage area	Keep out of frost.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

Ethylacetate (141-78-6)	
Australia - Occupational Exposure Limits	
Local name	Ethyl acetate (Acetic acid ethyl ester; Acetic ester)
OES TWA [1]	720 mg/m³
OES TWA [2]	200 ppm
OES STEL	1440 mg/m³
OES STEL [ppm]	400 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)

Toluene (108-88-3)	
Australia - Occupational Exposure Limits	
Local name	Toluene
OES TWA [1]	191 mg/m³
OES TWA [2]	50 ppm
OES STEL	574 mg/m³
OES STEL [ppm]	150 ppm
Remark (AU)	Sk - Absorption through the skin may be a significant source of exposure.
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)

Propan-2-ol (67-63-0)	
Australia - Occupational Exposure Limits	
Local name	Isopropyl alcohol (Propan-2-ol)
OES TWA [1]	983 mg/m³
OES TWA [2]	400 ppm
OES STEL	1230 mg/m³
OES STEL [ppm]	500 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)

8.2. Biological Monitoring

No additional information available

8.3. Engineering controls

Appropriate engineering controls Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection Chemically resistant protective gloves

Eye protection tightly fitting safety goggles

Skin and body protection Wear suitable protective clothing

Respiratory protection [In case of inadequate ventilation] wear respiratory protection.

Environmental exposure controls Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1 Information on Physical and Chemical Properties

Physical state	Liquid
Appearance	No data available
Colour	Cloudy
Odour	sweet odor
Odour Threshold	No data available
pH	No data available
pH solution	No data available
Relative evaporation rate (butylacetate=1)	No data available
Melting point / Freezing point	No data available
Boiling point	77 °C
Flash point	-2.7 °C
Auto-ignition temperature	No data available
Flammability (solid, gas)	No data available
Vapour pressure	Vapour pressure: 76 mm Hg
Relative density	No data available
Density	Relative density: 8
Solubility	No data available
Log Pow	No data available

Explosive properties	No data available
Explosive limits	No data available
Minimum ignition energy	No data available
Fat solubility	No data available

SECTION 10: Stability and reactivity

Reactivity	Highly flammable liquid and vapour.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No dangerous reactions known under normal conditions of use.
Conditions to avoid	Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Keep out of reach of children.
Incompatible materials	Strong oxidizing agent. Strong alkalis.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

Ethylacetate (141-78-6)	
LD50 oral	4934 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 20000 mg/kg bodyweight Animal: rabbit, Animal sex: male

Skin corrosion/irritation	Not classified
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Suspected of damaging the unborn child.
STOT-single exposure	May cause drowsiness or dizziness.

Ethylacetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.
Toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.
Propan-2-ol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure	Not classified

Ethylacetate (141-78-6)	
LOAEL (oral, rat, 90 days)	3600 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
NOAEL (oral, rat, 90 days)	900 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)

Toluene (108-88-3)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Not classified

Ethylacetate (141-78-6)	
Animal studies and expert judgment for classification	False

Toluene (108-88-3)	
Animal studies and expert judgment for classification	False

Propan-2-ol (67-63-0)	
Animal studies and expert judgment for classification	False

SECTION 12: Ecological information

12.1. Ecotoxicity

Ecology - general The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short–term (acute) Not classified

Hazardous to the aquatic environment, long–term (chronic) Not classified

Ethylacetate (141-78-6)	
LC50 fish 1	230 mg/l Test organisms (species): Pimephales promelas
NOEC (chronic)	2.4 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Propan-2-ol (67-63-0)	
LC50 fish 1	10000 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	9640 mg/l Pimephales promelas

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone Not classified

Other adverse effects No additional information available

XPEL Edge Prep Marker	
Fluorinated greenhouse gases	False
Ethylacetate (141-78-6)	
Fluorinated greenhouse gases	False
Toluene (108-88-3)	
Fluorinated greenhouse gases	False
Propan-2-ol (67-63-0)	
Fluorinated greenhouse gases	False

SECTION 13: Disposal considerations

Waste treatment methods Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information Flammable vapours may accumulate in the container.

SECTION 14: Transport information

14.1. UN number

UN-No. (ADG) 1133

UN-No. (IMDG) 1133

UN-No. (IATA) 1133

14.2. UN Proper Shipping Name

Proper Shipping Name (ADG) ADHESIVES

Proper Shipping Name (IMDG) ADHESIVES

Proper Shipping Name (IATA) Adhesives

14.3. Transport hazard class(es)

ADG

Transport hazard class(es) (ADG) 3

Danger labels (ADG) 3

IMDG

Transport hazard class(es) (IMDG) 3

Danger labels (IMDG) 3

IATA

Transport hazard class(es) (IATA)	3
Danger labels (IATA)	3

14.4. Packing group

Packing group (ADG)	II - Substances presenting medium danger
Packing group (IMDG)	II
Packing group (IATA)	II

14.5. Environmental hazards

Marine pollutant	No
Dangerous for the environment	No
Other information	No supplementary information available

14.6. Special precautions for user

Specific storage requirement	No data available
Shock sensitivity	No data available

14.7. Additional information

Other information	No supplementary information available

Transport by road and rail

UN-No. (ADG)	1133
Limited quantities (ADG)	5l
Excepted quantities (ADG)	E2
Packing instructions (ADG)	P001, IBC02
Special packing provisions (ADG)	PP1
Portable tank and bulk container instructions (ADG)	T4
Portable tank and bulk container special provisions (ADG)	TP1, TP8

Transport by sea

UN-No. (IMDG)	1133
Limited quantities (IMDG)	5 L
Excepted quantities (IMDG)	E2
Packing instructions (IMDG)	P001
Special packing provisions (IMDG)	PP1
IBC packing instructions (IMDG)	IBC02
Tank instructions (IMDG)	T4
Tank special provisions (IMDG)	TP1, TP8

EmS-No. (Fire)	F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG)	B

Air transport

UN-No. (IATA)	1133
PCA Excepted quantities (IATA)	E2
PCA Limited quantities (IATA)	Y341
PCA limited quantity max net quantity (IATA)	1L
PCA packing instructions (IATA)	353
PCA max net quantity (IATA)	5L
CAO packing instructions (IATA)	364
CAO max net quantity (IATA)	60L
Special provisions (IATA)	A3
ERG code (IATA)	3L

14.8. Hazchem or Emergency Action Code

Hazchem Code	* 3Y

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

15.2. International agreements

No additional information available

SECTION 16: Other information

Abbreviations and acronyms

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association

IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties
DOT	Department of Transport
TDG	Transportation of Dangerous Goods
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
GIS	Globally Harmonized System of Classification, Labelling and Packaging of Chemicals
ICB-Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
MARPOL 73/78 - MARPOL 73/78	International Convention for the Prevention of Pollution From Ships
ADG	Transport of Australian Dangerous Goods

Other information

Data of sections 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities. The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge. The delivery specifications are contained in the corresponding product sheet. This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

Classification	
Flam. Liq. 2	H225
Eye Irrit. 2A	H319
Repr. 2	H361
STOT SE 3	H336

Full text of H-statements	
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure