


TYPICAL SECTION
N.T.S.

SUBDIVISION WITH LESS THAN OR EQUAL TO 10 LOTS.
MAX. ALLOWABLE DESIGN SPEED – 30 MPH

1. ALL DIMENSIONS SHOWN ARE MINIMUM.
2. SEE APPROPRIATE SECTIONS OF TECHNICAL MANUAL FOR DESIGN PARAMETERS.
- * 3. PROVIDE 2' MINIMUM CLEARANCE FROM FENCES, WALLS, HEDGES, ABOVE GROUND UTILITIES OR IMPROVEMENTS, DROP OFFS, OR FROM THE TOPS OF BANKS WITH SLOPES STEEPER THAN 1 TO 4.
4. SOD SHALL BE PLACED IN TWO ROWS STAGGERED. (BOTH TEMPORARY AND PERMANENT)
5. PAVED SHOULDER TO BE STRIPED AS A DESIGNATED BIKE LANE, AS APPROPRIATE.



RIBBON CURB DETAIL
N.T.S.

REVISION DATE:

10/17

**TRANSPORTATION
TECHNICAL
MANUAL**



**Hillsborough
County Florida**

**LOW VOLUME PUBLIC ROADS (MINOR SUBDIVISIONS
WITH LESS THAN OR EQUAL TO 10 LOTS)
TYPICAL SECTION**

DRAWING NO. **TS-9**

SHEET NO. 1 OF 1