

Hurricane Guard

Our highest rated vinyl impact product for Florida's stringent requirements with exceptional everyday performance.



· Easy hurricane protection

Give your customer peace of mind with CWS Hurricane Guard impactresistant windows and patio doors, tested to withstand Florida hurricanes and the most stringent coastal requirements. CWS Hurricane Guard has options that will meet the requirements of nearly any project and will help protect your customer's home and everything inside. No additional storm preparation is required for our products, simply close and lock them.1 It's that simple.

Built for Florida and the HVHZ

CWS brings the right products to the right locations. CWS Hurricane Guard offers options tested to meet or exceed the strictest requirements of the Florida Building Code. Available options are rated to be installed in all coastal areas, including the High Velocity Hurricane Zone (HVHZ). CWS Hurricane Guard is our highest-rated and most complete hurricane impact-resistant product line.

Intentionally strong and energy efficient frame

With up to 18 insulating chambers and recessed sash design, our windows have been intentionally designed for structural strength, storm safety, comfort and energy efficiency. Our windows with laminated glass block nearly 100% of UV rays.

Improved protection from intruders and noise

Impact glass reduces more noise than standard glass, from the storm to everyday nuisances like traffic. Deter intruders with shatter-resistant, laminated glass and our recessed sash design on single-hung and sliding windows and anti-lift blocks on sliding patio doors.

Full product offering

Our wide array of product styles, sizes, shapes and configurations offer the right product for virtually every project. Choose from numerous product styles, shapes and the smallest 8" window to the largest 40' doors to meet your project needs.

Easy and accurate installation

Factory-drilled installation locations based on testing and requirements to create an easy and accurate installation experience.

Testing beyond requirements

Choose CWS Hurricane Guard windows with confidence. At CWS, our products are tested to meet or exceed industry requirements, testing not only the entire window for strength and durability, but individual parts as well. Ensuring long-lasting performance to reduce call-backs for you.

Limited lifetime warranty

CWS products are backed by some of the strongest warranties in the business. See written limited warranty for details, including exceptions and limitations, at cws.cc/downloads/.

AVAILABLE IN THESE WINDOW & PATIO DOOR STYLES:



















PRODUCT SPECIFICATIONS

						PERFORMANCE VALUES —			
WINDOW AND PATIO DOOR STYLES	MIN. WIDTH	MIN. HEIGHT	MAX. WIDTH	MAX. HEIGHT	DESIGN PRESSURE	U-FACTOR	SHGC	HVHZ	FL#
SINGLE-HUNG	13.5"	21"	52"	96"	+/-50 - +/-70	.3049	.1348	Yes	4091, 5823, 18689, 17647, 16177, 17339
SLIDING	21"	13.5"	125.625"	63"	+/-35 - +/-60	.3050	.1361	Yes	4092, 16735, 16736
CASEMENT	17.875"	20"	37"	72"	+/-60 - +/-70	.2647	.1151	Yes	4452, 6890, 17388
AWNING	20"	17.875"	48"	36"	+/-65 - +/-67.5	.2643	.1051	Yes	15032, 7060
DIRECT SET	8"	12"	84"	96"	+/-40 - +/-75	.2350	.1368	Yes	4093, 13010, 17387
SPECIAL SHAPES	8"	12"	96"	120"	+/-40 - +/-75	.2350	.1368	Yes	4093, 13010, 17387
SLIDING PATIO DOOR	59.5"	79.5"	190.125"	95.5"	+/-55 - +/-70	.2673	.1168	Yes	13241, 18561, 14849, 11103, 17338, 10272, 14848
HINGED PATIO DOOR	19.875"	36"	151.375"	97"	+/-60 - +/-90	.3247	.1159	Yes	16055, 16093
MULTISLIDE PATIO DOOR	50.735"	36"	580.0421"	120"	+/-65 - +/-80	.3050	.1253	Yes	20834, 20838

Window sizes available in 1/8" increments

Special shapes available. For more information regarding performance, specific sizes, glazings tested and frame and installation types, visit cws.cc.

Colors & Finishes

Frame Color

Create a signature look with a solid-color frame. A solid color throughout the vinyl formula keeps minor dings and scratches virtually invisible. Or add design interest with dual-color frames, featuring a White interior frame and a Bronze exterior.







Dual-Colors:



Bronze/White

Glass Options

Low-E Glass

Our glass collection offers energy saving choices to keep your home comfortable year-round.









Additional **Glass Options**

Additional glass options provide added benefits, such as more strength, improved energy efficiency or additional design options.

Low-E 366 Neat® Glass

Gray-Tinted

Rain

Frosted

Obscure

Tempered

Grilles

Grilles Types

Grilles are color-matched to your window or patio door interior and exterior frame color.





Exterior Applied Grilles with Grilles-Between-the-Glass:

7/8" Contour Exterior Applied Grille with 1" Contour Grilles-Between-the-Glass

Grille Patterns

Choose from one of our standard grille patterns or create a unique look with custom patterns.²



6-Lite



Prairie







Custom

Casement & Awning

Window Hardware

Low-profile handle creates a clean look inside your home. Stainless steel hinges and a zinc fold-away crank withstand harsh coastal spray.



Fold-Away Crank



White

Bronze

Sliding & Single-Hung

AutoLock hardware automatically locks the window when it is shut, simply close the sash and confirm it latches.



AutoLock



White

Bronze

²See back cover for disclosures

Sliding and Multi-Slide Patio Door

Stainless steel hardware withstands harsh coastal salt spray. Recessed Patio Door handle also available for multi-slide patio doors.





Hinged Patio Door

Stainless steel hardware withstands harsh coastal salt spray. Available with up to 6-point locking system for maximum security.



Screens³

BetterVue® Window Screen

Roll form or extruded screen available. BetterVue offers 10% better insect protection, 20% better airflow and 10% clearer view.⁴ The BetterVue screen will not rust, corrode or stain.

¹ No additional preparation needed to comply with most local impact requirements.

 $^{^{2}}$ Grille patterns offered may vary per product. See specific product information for availability.

³ Warning: Screens will not stop children or pets from falling out of window or door. Keep children or pets away from open window or door.

⁴ Improved airflow is based on calculated screen cloth openness. Screen cloth transmittance was measured using an integrated sphere spectrophotometer.