Pella 150 Series VINYL

Pella +

Quality vinyl windows and patio doors, backed by Pella.



LONG-LASTING, QUALITY VINYL FRAMES

Pella 150 Series windows and patio doors use a precision welding process to help resist warping and twisting. Our easy-care vinyl also uses a fade-resistant formula that is performance-tested for excellent weathering, durability and color retention.

EASIER INSTALLATION

To reduce installation time, block frame double-hung windows come with factory-applied perimeter foam insulation and sliding patio doors come fully assembled. Complete installation directions are available at installpella.com.

INCREASED ENERGY EFFICIENCY

Pella 150 Series windows offer solutions that will meet or exceed ENERGY STAR® guidelines in all 50 states.¹

ALL-METAL LOCKING HARDWARE

Anchored to the sash, all-metal locking hardware enhances security and ensures long-lasting, dependable operation.

SLEEK TILT LATCH DESIGN³

Tilt latches blend with the window sash design and make it easy to clean the exterior of a window from inside the home.

CONVENIENCE AND PRIVACY SOLUTIONS⁴

Add privacy with blinds-between-the-glass on sliding patio doors. Permanently sealed between panes of glass, they never need cleaning and are protected from damage.


LIMITED LIFETIME WARRANTY⁵

Give your customers peace of mind knowing these products are backed by Pella, a leader in the window and door industry for nearly 100 years. Pella 150 Series windows and sliding patio doors are backed by one of the best warranties in the business.

TESTED BEYOND REQUIREMENTS

At Pella, our products are tested beyond requirements to help ensure they have long-lasting performance.

AVAILABLE IN THESE WINDOW & PATIO DOOR STYLES1:



EAST REGION

						PERFORMANCE VALUES					
WINDOW & PATIO DOOR STYLES	MIN. WIDTH	MIN. HEIGHT	MAX. WIDTH	MAX. HEIGHT	PERFORMANCE CLASS & GRADE	U-FACTOR	SHGC	STC	FRAME / INSTALL		
SINGLE-HUNG WINDOW (DUAL-PANE) (VENT)	14-1/2"	23-1/2"	48"	84"	R20-LC65	0.29-0.47	0.21-0.65	25	Block Frame Nail Fin Nail Fin with J-Channel Integral 5/8" Flange (Florida only)		
DOUBLE-HUNG WINDOW (DUAL-PANE) (VENT)	14 -1/2"	23-1/2"	48"	78"	R25-R50	0.30-0.47	0.19-0.60	25-26	Block Frame Nail Fin Nail Fin with J-Channel		
SLIDING WINDOW (2-PANEL) (DUAL-PANE) (VENT)	21-1/2"	14-1/2"	73-1/2"	60"	R20-R35	0.29-0.47	0.20-0.64	26	Block Frame Nail Fin Nail Fin with J-Channel Integral 5/8" Flange (Florida only)		
SLIDING PATIO DOOR (DUAL-PANE) (VENT)	46-1/2"	70-1/2"	95-1/2"	95-1/2"	R35-R50	0.27-0.51	0.19-0.65	25	Nail Fin		
FIXED FRAME RECTANGLE (DUAL-PANE)	11-1/2"	11-1/2"	108"	108"	LC25-CW50	0.27-0.49	0.20-0.64	25	Block Frame Nail Fin Nail Fin with J-Channel Integral 5/8" Flange (Florida only)		

WEST REGION

	PERFORMANCE VALUES								1
WINDOW & PATIO DOOR STYLES	MIN. WIDTH	MIN. HEIGHT	MAX. WIDTH	MAX. HEIGHT	PERFORMANCE CLASS & GRADE	U-FACTOR	SHGC	STC	FRAME / INSTALL
SINGLE-HUNG WINDOW (DUAL-PANE) (VENT)	14-1/2"	29-1/2"	48"	84"	LC35	0.29-0.47	0.20-0.64	26	Block Frame Nail Fin Flush Flange
SLIDING WINDOW (2-PANEL) (DUAL-PANE) (VENT)	21-1/2"	9"	73-1/2"	60"	R20-R35	0.29-0.47	0.20-0.64	25	Block Frame Nail Fin Flush Flange
SLIDING PATIO DOOR (DUAL-PANE) (VENT)	46-1/2"	70-1/2"	95-1/2"	95-1/2"	R35	0.27-0.49	0.20-0.64	25	Nail Fin Flush Flange
FIXED FRAME RECTANGLE (DUAL-PANE)	11-1/2"	11-1/2"	108"	108"	LC25-CW50	0.27-0.48	0.22-0.69	26	Block Frame Nail Fin Flush Flange

WINDOW SIZES AVAILABLE IN 1/8" INCREMENTS

Maximum square footage rules apply. Maximum width and height cannot exceed the maximum square footage. Special shapes available. Visit pellaatlowes.com/150 for specific sizes and glazings tested and for more information regarding frame and installation types.

COLORS

FRAME COLORS

Create a signature look with solid-color frames.

SOLID-COLOR:

WHITE ALMOND® FOSSIL®

GRILLES

GRILLE TYPES

Grilles are color-matched to the window or patio door interior and exterior frame color.⁴





GRILLE PATTERNS

Choose from a variety of grille patterns for the traditional look of divided light. Grille patterns offered may vary by product. See specific product information for availability.









WINDOW HARDWARE

SLIDING, SINGLE-AND DOUBLE-HUNG

Pella's all-metal cam-action lock pushes the sashes against the weatherstripping for a tighter seal.









CAM-ACTION

AUTOLOCK West Region Only

INTEGRATED SASH LIFT

Make raising and lowering single- and double-hung window sashes easy with a standard, integrated sash lift.



WINDOW INTEGRATED

COLOR-MATCHED FINISHES:



WINDOW LIMITED **OPENING DEVICES**

A vent stop can be engaged or disengaged manually and restricts how far the bottom sash of a single- or double-hung window can open. A window opening control device (WOCD) complies with a safety standard and allows for ventilation, emergency escape and rescue when released. A WOCD automatically limits the sash opening to less than four inches, unless it is intentionally disengaged, enabling the sash to fully open.





COLOR-MATCHED FINISHES:



PATIO DOOR HARDWARE

SLIDING PATIO DOOR

Match the door's exterior color with a color-matched, corrosion-resistant handle, or upgrade the interior finish to add a touch of style.



SLIDING PATIO

COLOR-MATCHED FINISHES:



PATIO DOOR BLINDS

BLINDS-BETWEEN-THE-GLASS4

Add privacy and complement your project's decor with blinds-between-the-glass on sliding patio doors. Located between panes of glass, blinds are protected from dust, pets and damage.





NOTE: Product specifications may change without notice. Actual colors may vary from those shown and products may vary slightly from illustrations and photos.

¹Double-hung window available in East Region only.

² Some Pella products may not meet ENERGY STAR® guidelines in Canada. For more information, contact your local Pella sales representative or go to energystar.gc.ca.

 $^{^{\}rm 3}$ Available in the East Region Only

 $^{^4} Grilles\ are\ not\ available\ with\ blinds\ between\ the\ glass.\ Blinds\ between\ the\ glass\ available\ on\ sliding\ patio\ doors\ only.$

⁵The Pella Limited Lifetime Warranty is non-prorated, meaning the coverages within the defined warranty periods do not decrease over time. See written limited warranty for details, including exceptions and limitations, at pellaatlowes.com/support, or contact Pella Customer Service at 877-473-5527.

⁶ Available only in the West Region with nail fin frame.

 $^{^{7}}$ Appearance of exterior grille color may vary depending on the Low-E insulating glass selection.